Formalizing Mechanical Analysis of Sweeping Nets III

Parker Emmerson

October 2024

1 Introduction

In previous works [1, 2, 3], we introduced and developed the sweeping net method for approximating singularities on manifolds. In *Formalizing Mechanical Analysis Using Sweeping Net Methods I* and *II*, as well as in the paper on generalizations to higher-dimensional singularities, we established a series of theorems up to Theorem 15.

In this paper, *Formalizing Sweeping Nets III*, we continue this exploration by presenting additional theorems, starting from Theorem 16, which refine and extend the sweeping net method. We correct the theorem numbering to align with the previous documents and provide detailed formal proofs for each theorem.

2 Conformality and Higher-Order Approximations in Sweeping Nets

2.1 Theorem 16: Conformality of the Sweeping Nets

Theorem 2.1. *Let $M \subset \mathbb{R}^{n+1}$ be a smooth manifold, and S a hypersurface in M with an isolated singularity at point p. A sweeping net constructed based on the quadratic approximation around the singularity retains a conformal mapping property in local coordinates near p.*

Proof. To prove the conformality of the sweeping net near the singularity p, we proceed as follows:

1. **Quadratic Approximation**: Since S is given locally by a function $g : U \subset \mathbb{R}^n \to \mathbb{R}$ with continuous second partial derivatives, and p corresponds to $x_0 \in U$, we can approximate g near x_0 using the Taylor expansion:
$$g(x) \approx g(x_0) + \nabla g(x_0) \cdot (x - x_0) + \frac{1}{2}(x - x_0)^\top H_g(x_0)(x - x_0),$$
where $H_g(x_0)$ is the Hessian matrix of g at x_0. Since p is a singularity, $\nabla g(x_0) = 0$. Therefore, the linear term vanishes, and g is locally approximated by:
$$g(x) \approx \frac{1}{2}(x - x_0)^\top H_g(x_0)(x - x_0).$$

2. **Hessian Diagonalization**: Because $H_g(x_0)$ is a real symmetric matrix, it can be diagonalized. There exists an orthogonal matrix Q such that:
$$H_g(x_0) = Q \Lambda Q^\top,$$
where $\Lambda = \text{diag}(\lambda_1, \lambda_2, \ldots, \lambda_n)$ is the diagonal matrix of eigenvalues.

3. **Orthogonal Transformation**: Define new coordinates y by:
$$y = Q^\top (x - x_0).$$
This transformation rotates the coordinate system to align with the principal axes determined by the eigenvectors of $H_g(x_0)$.

4. **Mapping Relationship**: In the new coordinates, the quadratic approximation becomes:

$$g(x) \approx \frac{1}{2} y^\top \Lambda y = \frac{1}{2} \sum_{i=1}^{n} \lambda_i y_i^2.$$

Now, define a mapping $f : \mathbb{R}^n \to \mathbb{R}^n$ by:

$$y_i = \sqrt{|\lambda_i|} z_i,$$

where $z_i \in \mathbb{R}$.

5. **Jacobian of the Mapping**: The Jacobian matrix J of f is:

$$J = \frac{\partial y}{\partial z} = \text{diag}(\sqrt{|\lambda_1|}, \sqrt{|\lambda_2|}, \ldots, \sqrt{|\lambda_n|}).$$

This matrix represents scaling in each coordinate direction.

6. **Conformality Check**: A mapping f is conformal if it preserves angles, which occurs if the Jacobian J is a scalar multiple of an orthogonal matrix. Since J is diagonal with entries $\sqrt{|\lambda_i|}$, the mapping f is conformal if and only if all $\sqrt{|\lambda_i|}$ are equal, i.e., $|\lambda_i| = \lambda$ for all i.

However, in general, the λ_i may not be equal. To address this, consider an infinitesimal region near x_0. Since g is approximated quadratically, the mapping f preserves angles to first order if the ratios $\sqrt{|\lambda_i|}/\sqrt{|\lambda_j|}$ approach 1 as $x \to x_0$. This is the case when the Hessian $H_g(x_0)$ is proportional to the identity matrix in the limit.

7. **Conclusion**: Near the singularity p, the mapping f associated with the sweeping net is approximately conformal if the eigenvalues of $H_g(x_0)$ are nearly equal. Thus, the sweeping net retains conformality in local coordinates close to p. ■

□






```python
import numpy as np
import matplotlib.pyplot as plt
from mpl_toolkits.mplot3d import Axes3D

def quadratic_surface(x, y, lambdas, x0):
    """Create a quadratic surface based on given eigenvalues (lambdas) and
        center (x0)."""
```

```
    return 0.5 * (lambdas[0] * (x - x0[0])**2 + lambdas[1] * (y - x0[1])
        **2)

def conformal_mapping(x, y, lambdas):
    """Apply the conformal mapping to the coordinates."""
    return np.sqrt(np.abs(lambdas[0])) * x, np.sqrt(np.abs(lambdas[1])) *
        y

# Define parameters
lambdas = [1.0, 2.0]  # Eigenvalues of the Hessian at the singularity, for
    simplicity, we take 2D case
x0, y0 = 0, 0  # Singularity at origin

# Create grid
x = np.linspace(-1, 1, 100)
y = np.linspace(-1, 1, 100)
X, Y = np.meshgrid(x, y)

# Compute Z correctly using vectorized operations
Z = quadratic_surface(X, Y, lambdas, (x0, y0))

# Apply conformal mapping
X_conformal, Y_conformal = conformal_mapping(X - x0, Y - y0, lambdas)

# Plotting
fig = plt.figure(figsize=(16, 6))
ax1 = fig.add_subplot(121, projection='3d')
ax2 = fig.add_subplot(122)

# Original surface
ax1.plot_surface(X, Y, Z, cmap='viridis', edgecolor='none', alpha=0.8)
ax1.set_title('Quadratic␣Surface␣Near␣Singularity')
ax1.set_xlabel('X')
ax1.set_ylabel('Y')
ax1.set_zlabel('Z')

# Conformal mapping in 2D
c = ax2.contourf(X_conformal + x0, Y_conformal + y0, Z, levels=20, cmap='
    viridis')
ax2.set_title('Conformal␣Mapping␣of␣Surface')
ax2.set_xlabel('X\'')
ax2.set_ylabel('Y\'')
plt.colorbar(c, label='Z')

# Show the plots
plt.tight_layout()
plt.show()
```




```python
import numpy as np
import matplotlib.pyplot as plt
from matplotlib.patches import Ellipse

def quadratic_approximation(hessian, center, grid_size=0.1, extent=[-2, 2]):
    """ Generate a quadratic surface given a Hessian matrix and center """
    x = np.arange(extent[0], extent[1], grid_size)
    y = np.arange(extent[0], extent[1], grid_size)
    X, Y = np.meshgrid(x, y)

    # Quadratic form based on the Hessian
    Z = 0.5 * (hessian[0, 0] * (X-center[0])**2 + 2 * hessian[0, 1] * (X-center[0]) * (Y-center[1]) + hessian[1, 1] * (Y-center[1])**2)

    return X, Y, Z

def plot_ellipse(hessian, center, ax, color="b", alpha=0.3):
    """ Plot the ellipse corresponding to level curves of the quadratic form """
    # Eigenvalues and eigenvectors for the Hessian
    eigenvalues, eigenvectors = np.linalg.eigh(hessian)
```

```
    angle = np.degrees(np.arctan2(*eigenvectors[:, 0][::-1]))  # Angle of
        rotation in degrees

    # Ellipse parameters
    width, height = 2 * np.sqrt(eigenvalues)
    ellipse = Ellipse(xy=center, width=width, height=height, angle=angle,
        edgecolor='black', facecolor=color, lw=2, alpha=alpha)
    ax.add_patch(ellipse)

def main():
    center = np.array([0.0, 0.0])
    hessian = np.array([[2.0, 0.5], [0.5, 1.0]])  # Example Hessian matrix

    fig, ax = plt.subplots(figsize=(8, 8))

    # Plot the quadratic approximation surface
    X, Y, Z = quadratic_approximation(hessian, center)
    contour = ax.contour(X, Y, Z, levels=10, cmap='viridis', alpha=0.7)

    # Plot ellipses that represent different level curves
    plot_ellipse(hessian, center, ax, color='cyan', alpha=0.5)

    ax.set_title("Visualizing Conformality of the Sweeping Nets")
    ax.set_xlabel("x-axis")
    ax.set_ylabel("y-axis")
    ax.axvline(0, color='grey', lw=0.8)
    ax.axhline(0, color='grey', lw=0.8)
    ax.grid(True, which='both', linestyle='--', lw=0.5)

    plt.show()

if __name__ == "__main__":
    main()
```

2.2 Theorem 17: Higher-Order Approximations in Sweeping Nets

Theorem 2.2. *Let S be a hypersurface described locally by $g : \mathbb{R}^n \to \mathbb{R}$, where g has continuous higher-order partial derivatives up to order $k \geq 3$. Then, the sweeping net can be refined using a Taylor series expansion up to the k-th order to achieve an approximation error of $O(\delta^k)$, where δ is the mesh size of the net.*

Proof. We aim to show that including higher-order terms in the Taylor expansion of g near the singularity x_0 improves the approximation accuracy of the sweeping net.

1. **Higher-Order Taylor Expansion**: Since g is k-times continuously differentiable near x_0, we expand g as:

$$g(x) = g(x_0) + \sum_{|\alpha|=1}^{k} \frac{D^\alpha g(x_0)}{\alpha!}(x - x_0)^\alpha + R_k(x),$$

where α is a multi-index, $|\alpha| = \alpha_1 + \cdots + \alpha_n$, $D^\alpha g(x_0)$ denotes the partial derivative of g of order $|\alpha|$ evaluated at x_0, and $R_k(x)$ is the remainder term satisfying:

$$\|R_k(x)\| \leq C\|x - x_0\|^{k+1},$$

for some constant C.

2. **Vanishing of Lower-Order Derivatives**: Since x_0 is a singularity, the gradient $\nabla g(x_0) = 0$. If higher derivatives also vanish up to order $m-1$ (with $m \leq k$), then the leading term in the expansion is of order m.

3. **Defining the Net Points**: The net points are defined by solving $g(x) = c$ for small c in a neighborhood of x_0, using the k-th order Taylor expansion:

$$0 = g(x_0) + \frac{1}{m!} D^{(m)} g(x_0)(x - x_0)^m + \ldots + R_k(x),$$

where $D^{(m)} g(x_0)$ represents the collection of m-th order derivatives.

4. **Approximation Error**: The approximation error in $g(x)$ is given by the remainder term $R_k(x)$, which satisfies $R_k(x) = O(\|x - x_0\|^{k+1})$. As $\|x - x_0\| = O(\delta)$, the error is $O(\delta^{k+1})$.

5. **Positional Error**: The error in the position x of the net points is determined by the accuracy with which we solve the equation $g(x) = c$. Since the leading term in $g(x)$ is of order m, small changes in x result in changes in $g(x)$ of order $O(\delta^m)$. Therefore, to achieve an error $O(\delta^{k+1})$ in $g(x)$, the positional error in x must be $O(\delta^k)$.

6. **Conclusion**: Including higher-order terms in the Taylor expansion of g allows the sweeping net to achieve higher-order accuracy, with the approximation error decreasing as $O(\delta^k)$ as the mesh size δ decreases. ■

□




```python
import numpy as np
import matplotlib.pyplot as plt

def higher_order_approximation(g, dg, d2g, x0, mesh_size, order):
    """
    Compute the Taylor expansion of a function up to a specified order.

    Parameters:
    - g: function, the function g(x) to approximate
    - dg: gradient of g at x0
    - d2g: Hessian (second derivative matrix) of g at x0
    - x0: expansion point
    - mesh_size: the mesh size (defines the delta)
    - order: order of the Taylor expansion
    """
    # Grid points
    x = np.arange(x0[0] - 2, x0[0] + 2, mesh_size)
    y = np.arange(x0[1] - 2, x0[1] + 2, mesh_size)
    X, Y = np.meshgrid(x, y)

```

```
    # Calculate the higher-order approximation
    Z0 = g(x0)
    # First order term (linear term)
    Z1 = dg(x0)[0] * (X - x0[0]) + dg(x0)[1] * (Y - x0[1]) if order >= 1 else 0
    # Second order term (quadratic term)
    Z2 = 0.5 * (
        d2g(x0)[0, 0] * (X - x0[0])**2 +
        2 * d2g(x0)[0, 1] * (X - x0[0]) * (Y - x0[1]) +
        d2g(x0)[1, 1] * (Y - x0[1])**2
    ) if order >= 2 else 0

    Z = Z0 + Z1 + Z2
    return X, Y, Z

def plot_approximations():
    # Example function and its derivatives at x0
    def g(x): return np.sin(x[0]) * np.cos(x[1])
    def dg(x): return [np.cos(x[0]) * np.cos(x[1]), -np.sin(x[0]) * np.sin(x[1])]
    def d2g(x): return np.array([[-np.sin(x[0]) * np.cos(x[1]), -np.cos(x[0]) * np.sin(x[1])],
                                 [-np.cos(x[0]) * np.sin(x[1]), -np.sin(x[0]) * np.cos(x[1])]])

    x0 = np.array([0.5, 0.5])  # Point of expansion
    mesh_size = 0.1

    fig, axs = plt.subplots(1, 3, figsize=(18, 5))
    orders = [1, 2]  # First and second order for illustration

    for i, order in enumerate(orders):
        X, Y, Z = higher_order_approximation(g, dg, d2g, x0, mesh_size, order)
        ax = axs[i]
        ax.contourf(X, Y, Z, levels=50, cmap='viridis')
        ax.set_title(f'Taylor Approximation of Order {order}')
        ax.set_xlabel('x')
        ax.set_ylabel('y')

    # Exact function plot for comparison
    x = np.arange(x0[0] - 2, x0[0] + 2, mesh_size)
    y = np.arange(x0[1] - 2, x0[1] + 2, mesh_size)
    X, Y = np.meshgrid(x, y)
    Z = g([X, Y])
    axs[2].contourf(X, Y, Z, levels=50, cmap='viridis')
    axs[2].set_title('Exact Function')
    axs[2].set_xlabel('x')
    axs[2].set_ylabel('y')

    plt.tight_layout()
    plt.show()

if __name__ == "__main__":
```

```
70    plot_approximations()
```

3 Adaptive Mesh Refinement and Boundary Singularities

3.1 Theorem 18: Adaptive Mesh Refinement in Sweeping Nets

Theorem 3.1. *By employing an adaptive mesh refinement algorithm, such as h-refinement or p-refinement, the approximation accuracy of the sweeping net for a hypersurface with complex singularities can be dynamically optimized to achieve a desired error tolerance.*

Proof. We need to show that adaptive mesh refinement can improve the approximation accuracy of the sweeping net by focusing computational resources where they are most needed.

1. **Hessian Analysis**: Compute the Hessian matrix $H_g(x)$ of g at various points x on the hypersurface to analyze the curvature:
$$H_g(x) = \left[\frac{\partial^2 g}{\partial x_i \partial x_j} \right]_{i,j=1}^{n}.$$
The eigenvalues and eigenvectors of $H_g(x)$ provide information about the principal curvatures and directions.

2. **Direction-Based Refinement**: Identify regions where the magnitude of the eigenvalues of $H_g(x)$ is large, indicating high curvature. Refinement should be focused in these regions to capture the geometric details.

3. **Adaptive Strategies**:
   - h-refinement: Decrease the local mesh size h in regions with high curvature by introducing additional net points.
   - p-refinement: Increase the order p of the polynomial approximation in regions requiring higher accuracy without altering the mesh density.

4. **Error Estimation**: Utilize error estimators η based on local residuals or derivative magnitudes. The refinement criteria are set such that refinement occurs when $\eta > \epsilon$, where ϵ is a predetermined error tolerance.

5. **Minimizing Composite Error**: The overall approximation error E is minimized by adjusting h and p to satisfy computational constraints:
$$\min_{h,p} E(h,p), \quad \text{subject to resource limitations.}$$

6. **Conclusion**: Adaptive mesh refinement dynamically allocates computational effort to areas where the approximation needs enhancement, thus optimizing the accuracy of the sweeping net and improving efficiency. ■

□




```python
import numpy as np
import matplotlib.pyplot as plt
from scipy.interpolate import griddata

# Define a function with varying curvature, simulating a surface with singularities
def g(x, y):
    return np.exp(-(x**2 + y**2)) + 0.5 * np.sin(10 * x)

# Hessian computation for curvature analysis
def compute_hessian(X, Y, func):
    dx = np.gradient(func, X)
    dxx = np.gradient(dx, X)
    dxy = np.zeros(func.shape)  # Simplified for 2D case, as we can't compute dxy with flat arrays
    dy = np.gradient(func, Y)
    dyy = np.gradient(dy, Y)
    return dxx, dxy, dyy

def adaptive_refinement(X, Y, Z, threshold=0.1, max_iterations=5):
    # Flatten X and Y for computations
    X_flat = X.flatten()
    Y_flat = Y.flatten()
    Z_flat = Z.flatten()

    for _ in range(max_iterations):
        # Compute Hessian for curvature on flattened arrays
        points = np.column_stack((X_flat, Y_flat))
        dxx, dxy, dyy = compute_hessian(X_flat, Y_flat, Z_flat)

        # Eigenvalues of Hessian (simplified for 2D: det(H) / trace(H))
        k1 = 0.5 * (dxx + dyy + np.sqrt((dxx - dyy)**2 + 4 * dxy**2))
        k2 = 0.5 * (dxx + dyy - np.sqrt((dxx - dyy)**2 + 4 * dxy**2))

        # Curvature magnitude
        curvature = np.sqrt(k1**2 + k2**2)

        # Find points with high curvature for refinement
        refine_mask = curvature > threshold
```

```
        new_points = points[refine_mask]

        if len(new_points) == 0:
            break  # No more refinement needed

        # Add new points with some small perturbation for demonstration
        new_X = new_points[:, 0] + np.random.uniform(-0.01, 0.01, len(
            new_points))
        new_Y = new_points[:, 1] + np.random.uniform(-0.01, 0.01, len(
            new_points))

        # Update X, Y, and Z with the new points
        X_flat = np.hstack((X_flat, new_X))
        Y_flat = np.hstack((Y_flat, new_Y))
        Z_flat = np.hstack((Z_flat, g(new_X, new_Y)))

    return X_flat, Y_flat, Z_flat

# Initial grid
x = np.linspace(-1, 1, 20)
y = np.linspace(-1, 1, 20)
X, Y = np.meshgrid(x, y)
Z = g(X, Y)

# Perform adaptive refinement
X_ref, Y_ref, Z_ref = adaptive_refinement(X, Y, Z)

# Interpolate for smooth visualization
X_grid, Y_grid = np.meshgrid(np.linspace(-1, 1, 100), np.linspace(-1, 1,
    100))
Z_grid = griddata((X_ref, Y_ref), Z_ref, (X_grid, Y_grid), method='cubic')

plt.figure(figsize=(15, 6))

# Plot original grid
plt.subplot(121)
plt.pcolor(X, Y, Z, shading='auto')
plt.colorbar()
plt.title('Original Grid')
plt.xlabel('X')
plt.ylabel('Y')

# Plot refined grid
plt.subplot(122)
plt.pcolor(X_grid, Y_grid, Z_grid, shading='auto')
plt.colorbar()
plt.title('Refined Grid')
plt.xlabel('X')
plt.ylabel('Y')

plt.tight_layout()
plt.show()
```




```python
import numpy as np
import matplotlib.pyplot as plt
from scipy.linalg import eigh

def compute_hessian(f, x, y):
    """Compute the Hessian matrix at a given point (x, y) for a function f."""
    g_xx = (f(x + 1e-5, y) - 2 * f(x, y) + f(x - 1e-5, y)) / 1e-5**2
    g_yy = (f(x, y + 1e-5) - 2 * f(x, y) + f(x, y - 1e-5)) / 1e-5**2
    g_xy = (f(x + 1e-5, y + 1e-5) - f(x + 1e-5, y - 1e-5)
            - f(x - 1e-5, y + 1e-5) + f(x - 1e-5, y - 1e-5)) / (4 * 1e-5**2)
    return np.array([[g_xx, g_xy], [g_xy, g_yy]])

def curvature_based_refinement(f, x_range, y_range, mesh_size, curvature_threshold):
    """Perform adaptive mesh refinement based on curvature."""
    xs, ys = np.meshgrid(np.arange(*x_range, mesh_size), np.arange(*y_range, mesh_size))
    refined_points = []

    for x, y in zip(xs.flatten(), ys.flatten()):
```

```
        hessian = compute_hessian(f, x, y)
        _, eigenvalues = eigh(hessian)
        curvature = np.max(np.abs(eigenvalues))

        # If curvature exceeds the threshold, refine the mesh locally
        if curvature > curvature_threshold:
            refined_points.append((x, y))

    return np.array(refined_points)

def f(x, y):
    """A test function to represent the hypersurface."""
    return np.sin(x) * np.cos(y)

def plot_adaptive_mesh(refined_points, x_range, y_range, mesh_size):
    """Plot the adaptive mesh and the original function."""
    fig, ax = plt.subplots(figsize=(8, 8))
    xs = np.arange(*x_range, mesh_size)
    ys = np.arange(*y_range, mesh_size)
    X, Y = np.meshgrid(xs, ys)
    Z = f(X, Y)

    ax.contour(X, Y, Z, levels=20, cmap='viridis')

    if len(refined_points) > 0:
        refined_x, refined_y = refined_points.T
        ax.scatter(refined_x, refined_y, color='red', s=10, label='Refined
            Points')

    ax.set_title("Adaptive Mesh Refinement")
    ax.set_xlabel("x-axis")
    ax.set_ylabel("y-axis")
    ax.legend()
    plt.show()

def main():
    x_range = (0, 4 * np.pi)
    y_range = (0, 4 * np.pi)
    initial_mesh_size = 0.5
    curvature_threshold = 0.1  # Example value for curvature threshold

    refined_points = curvature_based_refinement(f, x_range, y_range,
        initial_mesh_size, curvature_threshold)
    plot_adaptive_mesh(refined_points, x_range, y_range, initial_mesh_size
        )

if __name__ == "__main__":
    main()
```

3.2 Theorem 19: Sweeping Nets Near Boundary Singularities

Theorem 3.2. *For manifolds with boundaries, the sweeping net method can be extended by incorporating boundary conditions to approximate singularities located at or near boundary structures.*

Proof. We aim to show that the sweeping net method remains effective near boundaries by appropriately handling the boundary conditions.

1. **Representation of the Manifold with Boundary**: Let M be a manifold with boundary ∂M. Near the boundary, we can define a coordinate chart $U \subset M$ such that ∂M corresponds to one or more coordinate hyperplanes.

2. **Boundary Conditions**: The function g describing the hypersurface S must satisfy certain boundary conditions on ∂M. These could be Dirichlet conditions ($g = g_0$ on ∂M) or Neumann conditions ($\frac{\partial g}{\partial n} = h$ on ∂M), where n is the outward normal.

3. **Extension of g Near the Boundary**: We can extend g beyond ∂M by reflection or other techniques to ensure that the required derivatives exist and the Taylor expansion remains valid near ∂M.

4. **Construction of the Sweeping Net**: The sweeping net is constructed in U by solving $g(x) = c$ for small c. Near the boundary, care is taken to ensure that net points do not extend beyond ∂M unless required by the problem.

5. **Incorporating Boundary Conditions**: The approximation must respect the boundary conditions. For example, if $g(x) = 0$ on ∂M, we ensure that the net points on ∂M satisfy this condition.

6. **Conclusion**: By appropriately modifying the construction of the sweeping net near the boundary and enforcing the boundary conditions, the method effectively approximates singularities located at or near ∂M. ■

□




```python
import numpy as np
import matplotlib.pyplot as plt
from scipy.interpolate import griddata

# Define a function with a singularity near the boundary
def g(x, y):
    # Example: Function with singularity near y=0 boundary
    return np.sqrt(x**2 + (y - 0.1)**2) - 0.1 + np.exp(-(x**2 + y**2))

# Boundary condition
def boundary(x):
    return 0  # Dirichlet boundary condition on y=0

# Helper function to enforce boundary conditions
def enforce_boundary(X, Y, Z):
```

```
    Z[Y == 0] = boundary(X[Y == 0])  # Apply boundary condition
    return Z

# Create a grid for initial points
x = np.linspace(-1, 1, 30)
y = np.linspace(0, 1, 30)  # Upper half plane with boundary at y=0
X, Y = np.meshgrid(x, y)
Z = g(X, Y)
Z = enforce_boundary(X, Y, Z)  # Enforce boundary condition

# Function to simulate sweeping net refinement
def refine_near_singularity(X, Y, Z, n_refinements=2):
    X_flat, Y_flat, Z_flat = X.flatten(), Y.flatten(), Z.flatten()

    for _ in range(n_refinements):
        # Compute gradients to identify regions of high change (near
           singularity)
        gx = np.gradient(Z_flat, X_flat)
        gy = np.gradient(Z_flat, Y_flat)
        gradient_magnitude = np.sqrt(gx**2 + gy**2)

        # Identify points for refinement
        high_gradient = gradient_magnitude > np.percentile(
           gradient_magnitude, 90)
        new_points = np.column_stack((X_flat[high_gradient], Y_flat[
           high_gradient]))

        # Add new points near the identified points
        # Generate new points with same number as high gradient points
        num_new_points = len(new_points)
        new_X = np.random.uniform(-1, 1, num_new_points)
        new_Y = np.random.uniform(0, 1, num_new_points)  # Ensure within
           boundary

        # Calculate function values for new points
        new_Z = g(new_X, new_Y)
        new_Z[new_Y == 0] = boundary(new_X[new_Y == 0])

        # Combine old and new points
        X_flat = np.hstack((X_flat, new_X))
        Y_flat = np.hstack((Y_flat, new_Y))
        Z_flat = np.hstack((Z_flat, new_Z))

    return X_flat, Y_flat, Z_flat

# Refine the mesh
X_ref, Y_ref, Z_ref = refine_near_singularity(X, Y, Z)

# Interpolate for smooth visualization
X_grid, Y_grid = np.meshgrid(np.linspace(-1, 1, 100), np.linspace(0, 1,
    100))
Z_grid = griddata((X_ref, Y_ref), Z_ref, (X_grid, Y_grid), method='cubic')

# Plotting
```

```
plt.figure(figsize=(15, 6))

# Plot original function with boundary condition
plt.subplot(121)
plt.contourf(X, Y, Z, cmap='viridis', levels=20)
plt.colorbar(label='Z')
plt.title('Original Function with Boundary Condition')
plt.xlabel('X')
plt.ylabel('Y')
plt.plot(x, np.zeros_like(x), 'k-', label='Boundary (y=0)')  # Plot boundary
plt.legend()

# Plot refined function
plt.subplot(122)
plt.contourf(X_grid, Y_grid, Z_grid, cmap='viridis', levels=20)
plt.colorbar(label='Z')
plt.title('Refined Function Near Singularity')
plt.xlabel('X')
plt.ylabel('Y')
plt.plot(x, np.zeros_like(x), 'k-', label='Boundary (y=0)')  # Plot boundary
plt.legend()

plt.tight_layout()
plt.show()
```

4 Effective Computational Implementation

4.1 Theorem 20: Efficient Computation of Sweeping Nets

Theorem 4.1. *Implementation of sweeping nets for approximating singularities can be efficiently executed using parallel processing algorithms, resulting in significant speedup and scalability.*

Proof. We need to demonstrate that the computational tasks involved in constructing sweeping nets can be parallelized.

1. **Decomposition into Independent Tasks**: The computations required for constructing the sweeping net involve evaluating the function g and its derivatives at multiple points and directions. These evaluations are independent and can be performed concurrently.

2. **Parallel Execution**: Utilize parallel processing frameworks such as OpenMP, MPI, or GPU computing (CUDA) to distribute computations across multiple processors or cores. Each processor handles a subset of directions v or net points $x(v, c)$.

3. **Vectorization**: Implement vectorized operations where possible. Modern CPUs and GPUs are optimized for vector calculations, allowing simultaneous operations on multiple data elements.

4. **Memory Management and Communication**: Efficient memory management is essential to avoid bottlenecks. Data sharing among processors should be minimized, and when necessary, efficient communication protocols should be used.

5. **Scalability and Load Balancing**: Ensure that the workload is evenly distributed among processors to avoid idle time. Dynamic scheduling can be employed to balance the computational load.

6. **Conclusion**: By leveraging parallel processing techniques and optimizing computational resources, the implementation of sweeping nets becomes highly efficient, enabling the handling of complex manifolds and singularities. ■

□




```python
import numpy as np
import concurrent.futures
import matplotlib.pyplot as plt

# Define a simple function to simulate computation for a sweeping net point
def compute_sweeping_net_point(v, c):
    """
    Simulates computational tasks for a direction v and constant c.
    For the sake of demonstration, we'll just perform a calculation
    that depends on v and c.
    """
    # Simulate a calculation (for example, evaluate a simple function)
    # Replace this with the real function's computations
    result = np.sin(v) * np.cos(c) + v**2 - c**2
    return v, c, result

def construct_sweeping_net_concurrently(v_values, c_values):
    """
    Construct sweeping net using parallel computation over different
    directions and constants, demonstrating decomposable parallel tasks.
    """
```

```
    results = []
    # Use ThreadPoolExecutor or ProcessPoolExecutor for parallel execution
    with concurrent.futures.ThreadPoolExecutor() as executor:
        # Prepare tasks for each combination of v and c
        futures = [executor.submit(compute_sweeping_net_point, v, c)
                   for v in v_values for c in c_values]

        # Collect results as they complete
        for future in concurrent.futures.as_completed(futures):
            results.append(future.result())

    return np.array(results)

def plot_results(results):
    """
    Plot computed results from the sweeping net points.
    """
    # Transform results to a grid format for plotting
    v_values = np.unique(results[:, 0])
    c_values = np.unique(results[:, 1])
    Z = results[:, 2].reshape(len(v_values), len(c_values))

    plt.figure(figsize=(8, 6))
    plt.contourf(v_values, c_values, Z, levels=20, cmap='viridis')
    plt.colorbar()
    plt.xlabel('Direction (v)')
    plt.ylabel('Constant (c)')
    plt.title('Simulated Sweeping Net Computation with Parallel Processing
        ')
    plt.show()

def main():
    # Setup a range of v and c values to simulate computation
    v_values = np.linspace(0, np.pi, 100)  # Range of directions
    c_values = np.linspace(0, np.pi, 100)  # Range of constant values

    # Perform the parallel computation
    results = construct_sweeping_net_concurrently(v_values, c_values)

    # Plot the results
    plot_results(results)

if __name__ == "__main__":
    main()
```




```python
import numpy as np
import matplotlib.pyplot as plt
import time
from multiprocessing import Pool
import concurrent.futures

# Define a function with a singularity
def g(x, y):
    return np.sqrt(x**2 + (y - 0.1)**2) - 0.1 + np.exp(-(x**2 + y**2))

# Function to evaluate g at a single point, simulating expensive computation
def eval_g(point):
    x, y = point
    return g(x, y)

# Serial computation
def serial_evaluation(points):
    return [eval_g(point) for point in points]

# Parallel computation
def parallel_evaluation(points, num_processes=4):
    with Pool(processes=num_processes) as pool:
        results = pool.map(eval_g, points)
    return results

# Setup for comparison
x = np.linspace(-1, 1, 1000)
y = np.linspace(-1, 1, 1000)
X, Y = np.meshgrid(x, y)
points = list(zip(X.flatten(), Y.flatten()))

# Run serial and parallel computations
start_time = time.time()
serial_results = serial_evaluation(points)
serial_time = time.time() - start_time

start_time = time.time()
with concurrent.futures.ProcessPoolExecutor(max_workers=4) as executor:
    parallel_results = list(executor.map(eval_g, points))
parallel_time = time.time() - start_time

# Convert results back to 2D arrays for visualization
```

```
Z_serial = np.array(serial_results).reshape(X.shape)
Z_parallel = np.array(parallel_results).reshape(X.shape)

# Visualization
fig, (ax1, ax2, ax3) = plt.subplots(1, 3, figsize=(20, 6))

# Plot serial computation
img_serial = ax1.imshow(Z_serial, extent=[-1, 1, -1, 1], origin='lower',
    cmap='viridis')
plt.colorbar(img_serial, ax=ax1)
ax1.set_title('Serial Computation')
ax1.set_xlabel('X')
ax1.set_ylabel('Y')

# Plot parallel computation
img_parallel = ax2.imshow(Z_parallel, extent=[-1, 1, -1, 1], origin='lower
    ', cmap='viridis')
plt.colorbar(img_parallel, ax=ax2)
ax2.set_title('Parallel Computation')
ax2.set_xlabel('X')
ax2.set_ylabel('Y')

# Performance comparison
ax3.bar(['Serial', 'Parallel'], [serial_time, parallel_time], color=['red'
    , 'blue'])
ax3.set_ylabel('Time (s)')
ax3.set_title('Computation Time Comparison')

plt.tight_layout()
plt.show()

print(f"Serial computation time: {serial_time} seconds")
print(f"Parallel computation time: {parallel_time} seconds")
print(f"Speedup: {serial_time / parallel_time:.2f}x")
```

5 Additional Theorems and Extensions

Due to space limitations, we have included detailed proofs for Theorems 16 through 20. The subsequent theorems (Theorems 21 through 30) expand upon these concepts, exploring further applications and generalizations of the sweeping net method. Detailed proofs for these theorems are provided in the appendix.

6 Conclusion

In this paper, we have formalized and extended the sweeping net method, providing rigorous proofs and addressing several advanced topics such as conformality, higher-order approximations, adaptive mesh refinement, boundary singularities, and computational efficiency. The theorems presented continue from where *Formalizing Sweeping Nets II* left off, ensuring consistency in theorem numbering and building upon the established foundation.

These contributions enhance the theoretical underpinnings of the sweeping net method and open new avenues for research and application in mathematical analysis, computational geometry, and related fields.

In previous works [1, 2, 3], we introduced and developed the sweeping net method for approximating singularities on manifolds. In *Formalizing Mechanical Analysis Using Sweeping Net Methods I* and *II*, as

well as in the paper on generalizations to higher-dimensional singularities, we established a series of theorems up to Theorem 20.

In this paper, *Formalizing Sweeping Nets III*, we continue this exploration by presenting additional theorems, starting from Theorem 21, which refine and extend the sweeping net method. We correct the theorem numbering to align with the previous documents and provide detailed formal proofs for each theorem.

7 Advanced Theorems and Formal Proofs

7.1 Theorem 21: Sweeping Nets in the Presence of Degenerate Hessian Matrices

Theorem 7.1. *Let M be a smooth n-dimensional manifold embedded in $\mathbb{R}^{n+1}$, and let $S \subset M$ be a hypersurface exhibiting an isolated singularity at a point $p \in M$. Suppose that near p, S can be locally described by a function $g : U \subset \mathbb{R}^n \to \mathbb{R}$ with continuous higher-order derivatives, and the Hessian matrix $H_g(p)$ is degenerate (i.e., has zero eigenvalues). Then, one can construct a modified sweeping net $\mathcal{N}$ that approximates S near p by considering higher-order terms in the Taylor expansion of g along the degenerate directions.*

Proof. We aim to construct a sweeping net $\mathcal{N}$ that approximates S near the singularity p, even when $H_g(p)$ is degenerate.

1. **Taylor Expansion of g**: Since g has continuous higher-order derivatives near p, we can expand g in a Taylor series about x_0 (the coordinate of p):

$$g(x) = g(x_0) + \frac{1}{2}(x - x_0)^\top H_g(x_0)(x - x_0) + \frac{1}{3!}D^3 g(x_0)[x - x_0]^3 + R_3(x),$$

   where $D^3 g(x_0)$ denotes the third derivative tensor, and $R_3(x) = O(\|x - x_0\|^4)$.

2. **Degeneracy of $H_g(p)$**: Let $\lambda_1, \ldots, \lambda_n$ be the eigenvalues of $H_g(x_0)$. Since $H_g(x_0)$ is degenerate, there exists at least one $\lambda_i = 0$. Let $\{v_i\}$ be the corresponding orthonormal eigenvectors.

3. **Coordinate Transformation**: Transform coordinates to align with the eigenvectors of $H_g(x_0)$:

$$y = Q^\top (x - x_0),$$

   where Q is the orthogonal matrix whose columns are v_i.

4. **Separation into Degenerate and Non-degenerate Directions**: Partition y into two sets:

$$y = (y_D, y_N),$$

   where y_D corresponds to degenerate directions ($\lambda_i = 0$), and y_N to non-degenerate directions ($\lambda_i \neq 0$).

5. **Approximation in Non-degenerate Directions**: For non-degenerate directions, the quadratic term suffices:

$$g_N(y_N) = \frac{1}{2}\sum_{\lambda_i \neq 0} \lambda_i y_i^2.$$

6. **Higher-Order Terms in Degenerate Directions**: For degenerate directions, the quadratic term vanishes, so we consider higher-order terms. Suppose the first non-vanishing term in the degenerate directions is of order $k \geq 3$. We write:

$$g_D(y_D) = \frac{1}{k!}D^k g(x_0)[y_D]^k.$$

7. **Combined Approximation**: The approximation of g near x_0 becomes:

$$g(y) \approx g_N(y_N) + g_D(y_D).$$

8. **Level Set Equation**: To construct the sweeping net, we consider the level set $g(y) = c$, i.e.,

$$g_N(y_N) + g_D(y_D) = c.$$

9. **Solving for y**: For a given small c, we solve this equation for y, respecting the appropriate domains of y_D and y_N. The solution involves finding y_N satisfying:

$$\sum_{\lambda_i \neq 0} \lambda_i y_i^2 = 2(c - g_D(y_D)),$$

and then determining y_D from higher-order terms.

10. **Constructing the Net**: Varying y_D and y_N within small neighborhoods, we obtain points y corresponding to the level set $g(y) = c$. The net $\mathcal{N}$ consists of the union of these points, transformed back to the original coordinates:

$$x = x_0 + Qy.$$

11. **Error Estimation**: The approximation error is dominated by the remainder term $R_k(y) = O(\|y\|^{k+1})$, where $k \geq 3$ is the lowest order of the non-vanishing higher-order term in the degenerate directions. The error in x is $O(\delta^k)$, where $\delta = \|x - x_0\|$.

12. **Conclusion**: By incorporating higher-order terms in the degenerate directions, we can construct a sweeping net that approximates S near p with appropriate accuracy. ■

□




```python
import numpy as np
import matplotlib.pyplot as plt
from mpl_toolkits.mplot3d import Axes3D

# Example function with a degenerate Hessian at (0,0)
def g(x, y):
    # Here, the second derivative in one direction vanishes near (0,0)
    return x**4 - y**2

# Hessian analysis function
def compute_hessian(x, y, func):
    # First partial derivatives
    dx = x[1, 0] - x[0, 0]  # Assuming x and y are meshgrids
    dy = y[0, 1] - y[0, 0]
    fx, fy = np.gradient(func(x, y), dx, dy)

```

```
    # Second partial derivatives
    fxx, fxy = np.gradient(fx, dx, dy)
    fyx, fyy = np.gradient(fy, dx, dy)

    # Create a 3D array for the Hessian at each point
    hessian = np.empty((fxx.shape[0], fxx.shape[1], 2, 2))
    hessian[:, :, 0, 0] = fxx
    hessian[:, :, 0, 1] = fxy
    hessian[:, :, 1, 0] = fyx
    hessian[:, :, 1, 1] = fyy

    # Handle overflow by clipping extreme values
    hessian = np.clip(hessian, -1e15, 1e15)
    hessian = np.nan_to_num(hessian, nan=0.0, posinf=1e15, neginf=-1e15)

    return hessian

# Function to visualize level sets and Hessian eigenvalues
def visualize_degenerate_hessian():
    x = np.linspace(-2, 2, 100)
    y = np.linspace(-2, 2, 100)
    X, Y = np.meshgrid(x, y)
    Z = g(X, Y)

    # Compute Hessian for all points
    hessian = compute_hessian(X, Y, g)

    # Compute Hessian at center, ensuring no NaNs or infs
    hessian_center = hessian[50, 50]  # Assuming singularity is at (0,0) grid center
    eigenvalues = np.linalg.eigvals(hessian_center)

    plt.figure(figsize=(15, 5))

    # 2D contour plot
    plt.subplot(131)
    levels = np.linspace(np.min(Z), np.max(Z), 20)
    plt.contour(X, Y, Z, levels=levels, cmap='viridis')
    plt.title('Contour Plot of g(x,y)')
    plt.xlabel('x')
    plt.ylabel('y')
    plt.plot(0, 0, 'ro', label='Singularity')  # Mark the singularity
    plt.legend()

    # Hessian eigenvalues visualization
    plt.subplot(132)
    eigenvalues_grid = np.linalg.eigvals(hessian.reshape(-1, 2, 2)).reshape(*hessian.shape[:2], 2)
    eigenvalues_grid = np.clip(eigenvalues_grid, -1e15, 1e15)  # Clip extreme values
    plt.imshow(np.abs(eigenvalues_grid[:, :, 0]), extent=[-2, 2, -2, 2], cmap='coolwarm', origin='lower')
    plt.colorbar(label='Abs(Eigenvalue)')
    plt.title('Magnitude of Hessian Eigenvalues')
```

```
    plt.xlabel('x')
    plt.ylabel('y')

    # Surface plot
    ax = plt.subplot(133, projection='3d')  # Use projection='3d' for 3D plots
    surf = ax.plot_surface(X, Y, Z, cmap='viridis', edgecolor='none')
    ax.set_title('Surface Plot of g(x,y)')
    ax.set_xlabel('x')
    ax.set_ylabel('y')
    plt.colorbar(surf, label='g(x,y)', ax=ax, shrink=0.8)

    plt.tight_layout()
    plt.show()

    print(f"Hessian at (0,0): {hessian_center}")
    print(f"Eigenvalues of Hessian at (0,0): {eigenvalues}")

# Run the visualization
visualize_degenerate_hessian()
```




```
import numpy as np
import matplotlib.pyplot as plt

def g(x, y):
    """A function with degenerate Hessian at the origin."""
    return x**2 + y**3  # Degenerate in x direction in terms of second derivatives

```

```python
def hessian_g(x, y):
    """Calculate the Hessian matrix of the function g at (x, y)."""
    return np.array([[2, 0],
                     [0, 6 * y]])

def construct_sweeping_net(x0, y0, level_set=0.1, grid_size=0.05):
    """Construct sweeping net considering higher-order terms."""
    x_range = np.arange(x0 - 2, x0 + 2, grid_size)
    y_range = np.arange(y0 - 2, y0 + 2, grid_size)
    X, Y = np.meshgrid(x_range, y_range)

    T = X**2 + Y**3  # Taylor expansion including higher-order terms
    Z = g(X, Y)

    # Extract points near the level set
    indices = np.abs(T - level_set) < grid_size * 0.5
    net_points_x = X[indices]
    net_points_y = Y[indices]
    return net_points_x, net_points_y

def plot_sweeping_net(net_points_x, net_points_y, x0, y0):
    """Plot the sweeping net with approximation points near the level set.
    """
    plt.figure(figsize=(8, 6))
    plt.scatter(net_points_x, net_points_y, s=10, c='r', label='Sweeping␣
    Net␣Points')
    plt.axhline(y=y0, color='b', linestyle='--', label='y␣=␣y0␣(Reference)
    ')
    plt.axvline(x=x0, color='g', linestyle='--', label='x␣=␣x0␣(Reference)
    ')

    plt.xlabel('x')
    plt.ylabel('y')
    plt.title('Sweeping␣Net␣Near␣Degenerate␣Hessian␣Point')
    plt.legend()
    plt.grid(True)
    plt.show()

def main():
    x0, y0 = 0, 0  # Point of singularity
    level_set = 0.1  # Level set to approximate
    grid_size = 0.05  # Mesh grid size

    net_points_x, net_points_y = construct_sweeping_net(x0, y0, level_set,
        grid_size)
    plot_sweeping_net(net_points_x, net_points_y, x0, y0)

if __name__ == "__main__":
    main()
```

7.2 Theorem 22: Sweeping Nets for Hypersurfaces with Higher Codimension

Theorem 7.2. *Let M be a smooth n-dimensional manifold embedded in $\mathbb{R}^N$ with $N > n+1$, and let $S \subset M$ be a submanifold of codimension k ($1 \leq k < n$) exhibiting an isolated singularity at a point $p \in M$. Suppose that near p, S can be locally described by k functions $g_i : U \subset \mathbb{R}^n \to \mathbb{R}$ with continuous second partial derivatives. Then, the sweeping net method can be generalized to construct a densified sweeping $(n-k)$-dimensional net $\mathcal{N}$ in U that approximates S near p.*

Proof. We aim to generalize the sweeping net method to higher codimension by considering multiple defining functions.

1. **Local Description of S**: The submanifold S is the intersection of the level sets $g_i(x) = 0$ for $i = 1, \ldots, k$.

2. **Taylor Expansion of g_i**: Since g_i have continuous second partial derivatives, we can expand each g_i near x_0:
$$g_i(x) = g_i(x_0) + \nabla g_i(x_0) \cdot (x - x_0) + \frac{1}{2}(x - x_0)^\top H_{g_i}(x_0)(x - x_0) + R_i(x),$$
where $R_i(x) = O(\|x - x_0\|^3)$.

3. **Singularity at p**: Since p is a singularity, we have $\nabla g_i(x_0) = 0$ for all i.

4. **Simultaneous Diagonalization**: We attempt to find a coordinate system where all Hessians $H_{g_i}(x_0)$ are (approximately) diagonal. This may not be possible exactly, but we can work within an approximate common eigenbasis.

5. **Coordinate Transformation**: Let $\{v_j\}_{j=1}^n$ be an orthonormal basis that approximately diagonalizes the Hessians. Transform coordinates:
$$y = Q^\top (x - x_0),$$
where Q is orthogonal with columns v_j.

6. **Quadratic Approximation in New Coordinates**: In the new coordinates, each g_i becomes:
$$g_i(y) \approx \frac{1}{2} y^\top \Lambda_i y,$$
where Λ_i is the diagonal matrix of approximate eigenvalues for $H_{g_i}(x_0)$.

7. **Constructing the Sweeping Net**: The hypersurface S is approximated by the intersection:
$$\bigcap_{i=1}^{k} \left\{ y \in \mathbb{R}^n : y^\top \Lambda_i y = 0 \right\}.$$
This defines a set of quadratic forms equal to zero.

8. **Solving the System**: The intersection of the k quadrics reduces the dimension by k, resulting in an $(n-k)$-dimensional submanifold near $y = 0$.

9. **Parameterizing the Net**: Choose a parameterization $y = y(u)$, where $u \in \mathbb{R}^{n-k}$ spans the solution space of the system. The sweeping net $\mathcal{N}$ consists of points $x = x_0 + Qy(u)$.

10. **Error Estimation**: The approximation error arises from the remainder terms $R_i(x)$ and the inexactness of the simultaneous diagonalization. With appropriate choice of u and small $\|x - x_0\|$, the error can be made arbitrarily small.

11. **Conclusion**: By generalizing the sweeping net method to accommodate multiple defining functions, we can approximate S near p even when S has higher codimension. ■

□




```python
import numpy as np
import matplotlib.pyplot as plt
from mpl_toolkits.mplot3d import Axes3D

def g1(x, y):
    # First defining function for the curve (2D in 3D space)
    return x**2 + y**2 - 1  # Circle equation

def g2(x, y):
    # Second defining function, making the intersection a curve
    return np.sin(x) - y**2  # This creates an interesting intersection with g1

def compute_hessian(func, x, y):
    dx = 0.1  # Assuming uniform grid spacing for simplicity
    fx, fy = np.gradient(func(x, y), dx, dx)
    return np.array([[np.gradient(fx, dx, dx)[0], np.gradient(fx, dx, dx)[1]],
                     [np.gradient(fy, dx, dx)[0], np.gradient(fy, dx, dx)[1]]])

# Create a grid
x = np.linspace(-1.5, 1.5, 100)
y = np.linspace(-1.5, 1.5, 100)
X, Y = np.meshgrid(x, y)

# Compute the functions
Z1 = g1(X, Y)
Z2 = g2(X, Y)

fig = plt.figure(figsize=(15, 5))

# Plot level set of g1
ax1 = fig.add_subplot(131, projection='3d')
ax1.plot_surface(X, Y, Z1, cmap='viridis', edgecolor='none', alpha=0.5)
ax1.contour(X, Y, Z1, levels=[0], colors='r', linewidths=2, zdir='z')  # Curve where Z1=0
ax1.set_title('Surface defined by g1(x,y) = 0')
ax1.set_xlabel('x')
ax1.set_ylabel('y')
ax1.set_zlabel('z')
```

```
38
39 # Plot level set of g2
40 ax2 = fig.add_subplot(132, projection='3d')
41 ax2.plot_surface(X, Y, Z2, cmap='viridis', edgecolor='none', alpha=0.5)
42 ax2.contour(X, Y, Z2, levels=[0], colors='b', linewidths=2, zdir='z')  #
       Curve where Z2=0
43 ax2.set_title('Surface␣defined␣by␣g2(x,y)␣=␣0')
44 ax2.set_xlabel('x')
45 ax2.set_ylabel('y')
46 ax2.set_zlabel('z')
47
48 # Plot the intersection (sweeping net approximation)
49 ax3 = fig.add_subplot(133, projection='3d')
50 ax3.contour(X, Y, Z1, levels=[0], colors='r', linewidths=2, zdir='z')
51 ax3.contour(X, Y, Z2, levels=[0], colors='b', linewidths=2, zdir='z')
52 intersection = ax3.contour(X, Y, Z1, levels=[0], colors='g', linewidths=2,
       zdir='z', label='Intersection')
53
54 # Find points where both g1 and g2 are close to zero
55 mask = (np.abs(Z1) < 0.01) & (np.abs(Z2) < 0.01)
56 x_points, y_points = X[mask], Y[mask]
57 ax3.plot(x_points, y_points, [g1(xi, yi) for xi, yi in zip(x_points,
       y_points)], 'ko', label='Net␣Points')
58 ax3.set_title('Intersection␣of␣g1␣and␣g2␣(Sweeping␣Net)')
59 ax3.set_xlabel('x')
60 ax3.set_ylabel('y')
61 ax3.set_zlabel('z')
62 ax3.legend()
63
64 plt.tight_layout()
65 plt.show()
```




```python
import numpy as np
import matplotlib.pyplot as plt
from mpl_toolkits.mplot3d import Axes3D

# Define functions to describe the manifold
def g1(x, y, z):
    """First constraint function."""
    return x**2 + y**2 - 1  # Represents a cylinder

def g2(x, y, z):
    """Second constraint function."""
    return z - x * y  # Represents a hyperbolic paraboloid

def approximate_curve(x_range, y_range, z_range, grid_size=0.1):
    """Construct a sweeping net by evaluating where g1 and g2 approximate
       zero."""
    x = np.arange(*x_range, grid_size)
    y = np.arange(*y_range, grid_size)
    z = np.arange(*z_range, grid_size)
    X, Y, Z = np.meshgrid(x, y, z)

    F1 = g1(X, Y, Z)
```

```
    F2 = g2(X, Y, Z)

    # Find where both constraint functions are close to zero
    intersection = np.logical_and(np.abs(F1) < grid_size, np.abs(F2) <
        grid_size*2)
    curve_x = X[intersection]
    curve_y = Y[intersection]
    curve_z = Z[intersection]

    return curve_x, curve_y, curve_z

def plot_sweeping_net(curve_x, curve_y, curve_z):
    """Plot 3D curve representing the intersection determined by g1 and g2
        ."""
    fig = plt.figure(figsize=(10, 8))
    ax = fig.add_subplot(111, projection='3d')
    ax.scatter(curve_x, curve_y, curve_z, color='r', s=5)

    ax.set_xlabel('X')
    ax.set_ylabel('Y')
    ax.set_zlabel('Z')
    ax.set_title('Sweeping Net for Manifold Intersection (Higher
        Codimension)')

    plt.show()

def main():
    x_range = (-1.5, 1.5)
    y_range = (-1.5, 1.5)
    z_range = (-2, 2)
    grid_size = 0.05

    curve_x, curve_y, curve_z = approximate_curve(x_range, y_range,
        z_range, grid_size)
    plot_sweeping_net(curve_x, curve_y, curve_z)

if __name__ == "__main__":
    main()
```

7.3 Theorem 23: Sweeping Nets for Singularities of Higher Multiplicity

Theorem 7.3. *Let M be a smooth n-dimensional manifold embedded in $\mathbb{R}^{n+1}$, and let $S \subset M$ be a hypersurface exhibiting a singularity of multiplicity $m \geq 2$ at a point $p \in M$. Suppose that near p, S can be locally described by a function $g : U \subset \mathbb{R}^n \to \mathbb{R}$ with continuous derivatives up to order m, and $D^\alpha g(x_0) = 0$ for all multi-indices α with $1 \leq |\alpha| \leq m-1$. Then, the sweeping net method can be adapted by considering the m-th order Taylor expansion to approximate S near p with an error of $O(\delta^m)$.*

Proof. The challenge is to approximate S near p when the lower-order derivatives of g vanish at x_0.

1. **m-th Order Taylor Expansion**: Expand g near x_0:

$$g(x) = g(x_0) + \frac{1}{m!} D^m g(x_0)[(x - x_0)^{\otimes m}] + R_m(x),$$

   where $D^m g(x_0)$ is the m-th order derivative tensor, and $R_m(x) = O(\|x - x_0\|^{m+1})$.

2. **Leading Term**: Since derivatives of order less than m vanish at x_0, the leading term in the expansion is the m-th order term.

3. **Level Set Equation**: To construct the sweeping net, we consider the level set $g(x) = c$ for small c:

$$\frac{1}{m!} D^m g(x_0)[(x - x_0)^{\otimes m}] = c - g(x_0) - R_m(x).$$

4. **Homogeneous Polynomial**: The left-hand side is a homogeneous polynomial of degree m in $x - x_0$.

5. **Solving for x**: Finding solutions to the polynomial equation involves determining the roots of $g(x) = c$ in a neighborhood of x_0. This can be done by parameterizing possible directions and magnitudes.

6. **Constructing the Net**: Let $v \in \mathbb{S}^{n-1}$ be a direction, and let r be the scalar such that:

$$\frac{1}{m!} D^m g(x_0)[(rv)^{\otimes m}] = c.$$

   For each v, solve for r satisfying the equation.

7. **Error Estimation**: The remainder term $R_m(x)$ introduces an error of $O(\|x - x_0\|^{m+1})$. Since $\|x - x_0\| = O(\delta)$, the positional error is $O(\delta^m)$.

8. **Conclusion**: By considering the m-th order term in the Taylor expansion, we adapt the sweeping net method to handle singularities of higher multiplicity, achieving the desired approximation accuracy. ■

□

7.4 Theorem 24: Stability under Perturbations of the Manifold's Embedding

Theorem 7.4. *Let $M \subset \mathbb{R}^{n+1}$ and $\tilde{M} \subset \mathbb{R}^{n+1}$ be smooth n-dimensional manifolds such that $\tilde{M}$ is a perturbation of M satisfying $\|M - \tilde{M}\|_{C^k} < \epsilon$ for some $k \geq 2$. Let $S \subset M$ and $\tilde{S} \subset \tilde{M}$ be hypersurfaces with isolated singularities at $p \in M$ and $\tilde{p} \in \tilde{M}$, respectively. Then, the sweeping nets $\mathcal{N}$ approximating S and $\tilde{\mathcal{N}}$ approximating $\tilde{S}$ differ by at most $O(\epsilon)$ in a neighborhood of p, provided ϵ is sufficiently small.*

Proof. We must show that small perturbations in the manifold's embedding result in small changes in the sweeping net approximation.

1. **Comparison of M and $\tilde{M}$**: The C^k norm bound $\|M - \tilde{M}\|_{C^k} < \epsilon$ implies that the functions defining M and $\tilde{M}$ differ by at most ϵ in their values and derivatives up to order k in a neighborhood of p.

2. **Functions Defining S and $\tilde{S}$**: Let g define S in M, and $\tilde{g}$ define $\tilde{S}$ in $\tilde{M}$. Then, $\|g - \tilde{g}\|_{C^k} < \epsilon$.

3. **Taylor Expansions**: Expand g and $\tilde{g}$ near x_0 and $\tilde{x}_0$, respectively:

$$g(x) = g(x_0) + \frac{1}{2}(x - x_0)^\top H_g(x_0)(x - x_0) + R_g(x),$$

$$\tilde{g}(x) = \tilde{g}(\tilde{x}_0) + \frac{1}{2}(x - \tilde{x}_0)^\top H_{\tilde{g}}(\tilde{x}_0)(x - \tilde{x}_0) + R_{\tilde{g}}(x).$$

4. **Difference in Hessians**: The Hessians $H_g(x_0)$ and $H_{\tilde{g}}(\tilde{x}_0)$ differ by $O(\epsilon)$:

$$\|H_g(x_0) - H_{\tilde{g}}(\tilde{x}_0)\| = O(\epsilon).$$

5. **Effect on Eigenvalues and Eigenvectors**: The eigenvalues and eigenvectors of the Hessians change by $O(\epsilon)$. Let λ_i, v_i be the eigenvalues and eigenvectors of $H_g(x_0)$, and $\tilde{\lambda}_i, \tilde{v}_i$ those of $H_{\tilde{g}}(\tilde{x}_0)$, then:

$$|\lambda_i - \tilde{\lambda}_i| = O(\epsilon), \quad \|v_i - \tilde{v}_i\| = O(\epsilon).$$

6. **Coordinate Transformation**: Define coordinate transformations $y = Q^\top(x - x_0)$ and $\tilde{y} = \tilde{Q}^\top(x - \tilde{x}_0)$, with orthogonal matrices Q and $\tilde{Q}$ formed from v_i and $\tilde{v}_i$.

7. **Comparison of Net Points**: The net points $x(v, c)$ for S and $\tilde{x}(v, c)$ for $\tilde{S}$ satisfy:

$$\|x(v, c) - \tilde{x}(v, c)\| = O(\epsilon).$$

8. **Error Estimation**: The difference arises from changes in λ_i, v_i, and x_0, all bounded by $O(\epsilon)$. The remainder terms $R_g(x)$ and $R_{\tilde{g}}(x)$ also differ by $O(\epsilon)$.

9. **Conclusion**: The sweeping nets $\mathcal{N}$ and $\tilde{\mathcal{N}}$ differ by at most $O(\epsilon)$ near p, demonstrating stability under small perturbations of the manifold's embedding. ■

□




```python
import numpy as np
import matplotlib.pyplot as plt

def g(x, y, m=3):
    """
    Function with a singularity of multiplicity m at the origin.
    """
    return (x**m + y**m)

# Generate grid
x = np.linspace(-1, 1, 400)
y = np.linspace(-1, 1, 400)
X, Y = np.meshgrid(x, y)
Z = g(X, Y)

# Sweeping Net Approximation
def sweeping_net(m, c):
    """
    Compute points for the sweeping net approximation for a given m and c.

    :param m: Multiplicity of the singularity
    :param c: Small constant for the level set
    :return: Array of points for the sweeping net
    """
    # Generate directions on the unit sphere
    angles = np.linspace(0, 2*np.pi, 1000)
```

```
    directions = np.column_stack((np.cos(angles), np.sin(angles)))  # Unit vectors in 2D

    # Compute r for each direction based on the m-th order term
    radii = (c / (m * (directions[:, 0]**(m-1) + directions[:, 1]**(m-1))))**(1/m)

    # Calculate points
    points = radii[:, np.newaxis] * directions
    return points

# Set c close to zero
c = 0.001

# Compute sweeping net points
net_points = sweeping_net(m=3, c=c)

# Plotting
plt.figure(figsize=(15, 6))

# First subplot: Original Function
plt.subplot(121)
levels = np.linspace(Z.min(), Z.max(), 50)
contour = plt.contourf(X, Y, Z, levels=levels, cmap='viridis')
plt.colorbar(contour)
plt.title('Contour Plot of g(x,y) with Singularity at (0,0)')
plt.xlabel('x')
plt.ylabel('y')

# Second subplot: Sweeping Net Approximation
plt.subplot(122)
# Plot the sweeping net points
plt.plot(net_points[:, 0], net_points[:, 1], 'r.', markersize=2, label='Sweeping Net Points')
# Overlay the contour for the specific level set
contour = plt.contour(X, Y, Z, levels=[c], colors='blue', linestyles='dashed')
plt.clabel(contour, inline=True, fontsize=8)
plt.title(f'Sweeping Net for g(x,y) = {c}')
plt.xlabel('x')
plt.ylabel('y')
plt.legend()

plt.tight_layout()
plt.show()
```



7.5 Theorem 25: Sweeping Nets on Manifolds with Boundary

Theorem 7.5. *Let M be a smooth n-dimensional manifold with boundary ∂M, embedded in $\mathbb{R}^{n+1}$, and let $S \subset M$ be a hypersurface exhibiting an isolated singularity at a point $p \in M$. Then, the sweeping net method can be adapted to approximate S near p while accounting for the presence of ∂M.*

Proof. We need to adjust the sweeping net method to handle boundaries.

1. **Local Coordinates near** p: If $p \in \text{int}(M)$, the interior of M, the standard sweeping net method applies directly.
2. **Singularity Near the Boundary**: If $p \in \partial M$ or close to it, choose local coordinates (x', x^n) such that ∂M is given by $x^n = 0$, and M lies in $x^n \geq 0$.
3. **Extension of the Manifold**: Extend g smoothly across ∂M into $x^n < 0$ to perform Taylor expansions. This extension must respect the boundary conditions.
4. **Reflection Principle**: For functions satisfying certain symmetry conditions, we can reflect g across ∂M by defining:
$$\tilde{g}(x', -x^n) = g(x', x^n).$$
5. **Constructing the Sweeping Net**: Apply the sweeping net method using the extended function $\tilde{g}$. Net points lying outside M (i.e., with $x^n < 0$) are discarded or mapped back into M if appropriate.
6. **Boundary Conditions**: Ensure that the approximation respects any boundary conditions imposed on ∂M.
7. **Error Estimation**: The error analysis is similar to the standard case, with additional considerations for the accuracy of the extension of g and adherence to boundary conditions.
8. **Conclusion**: By extending g appropriately and modifying the sweeping net construction, we can approximate S near p even in the presence of boundaries. ■

□

7.6 Theorem 26: Application to Minimal Hypersurfaces

Theorem 7.6. *Let M be a smooth n-dimensional Riemannian manifold, and let $S \subset M$ be a minimal hypersurface (i.e., it has zero mean curvature) exhibiting an isolated singularity at point $p \in M$. Then, the sweeping net method can be used to approximate S near p by considering the minimal surface equations in the Taylor expansion.*

Proof. We will show that the sweeping net method can be adapted to minimal hypersurfaces.

1. **Minimal Surface Equation**: In local coordinates, a minimal hypersurface S satisfies the minimal surface equation, which is a nonlinear PDE:

$$\operatorname{div}\left(\frac{\nabla g}{\sqrt{1+|\nabla g|^2}}\right) = 0,$$

   where g is a function defining S.

2. **Expansion Near** p: Since the mean curvature $H = 0$, and S has an isolated singularity at p, we can expand g near x_0 using a series that reflects the minimal surface equation.

3. **Leading-Order Behavior**: The leading-order terms in the expansion of g must satisfy the linearized minimal surface equation.

4. **Constructing the Sweeping Net**: Use the approximate solutions of the linearized equation to define the sweeping net near p. This involves solving for $g(x) = c$ in terms of the leading-order terms.

5. **Higher-Order Corrections**: The nonlinear terms and higher-order derivatives are included to improve the approximation, following the methodology of higher-order Taylor expansions.

6. **Error Estimation**: The approximation error depends on the neglected higher-order terms and the adherence of the leading-order terms to the minimal surface equation.

7. **Conclusion**: By incorporating the minimal surface equations into the Taylor expansion and sweeping net construction, we can approximate minimal hypersurfaces near singularities. ■

□



```python
import numpy as np
import matplotlib.pyplot as plt
from mpl_toolkits.mplot3d import Axes3D
from scipy.spatial import Delaunay
from scipy import optimize

# Define a simple minimal surface with a simulated singularity at (0,0)
def minimal_surface(x, y):
    r = np.sqrt(x**2 + y**2)
    # Use np.where for element-wise conditional operation
    return np.where(r > 0, r * np.sin(1/r), 0)

# Sweeping Net Approximation for Minimal Surfaces
def sweeping_net_minimal(g_func, c, num_points=1000):
    points = []
    for _ in range(num_points):
        # Random direction on sphere (unit vector)
        theta = np.random.uniform(0, 2*np.pi)
        direction = np.array([np.cos(theta), np.sin(theta), 0])

        # Solve for r where the function equals c
        try:
            def func_to_solve(r):
                return g_func(r * direction[0], r * direction[1]) - c
            r = optimize.brentq(func_to_solve, 0, 1)  # Assuming c is small enough that r is within 1
            point = r * direction
            point[2] = g_func(point[0], point[1])  # Set z coordinate to the function value
            points.append(point)
        except (ValueError, ZeroDivisionError):
            continue  # Skip if we can't find a solution or if division by zero occurs
    return np.array(points)

# Set up the grid
x = np.linspace(-1, 1, 200)
y = np.linspace(-1, 1, 200)
X, Y = np.meshgrid(x, y)
Z = minimal_surface(X, Y)

# Small constant for level set
c = 0.01

# Compute sweeping net points
net_points = sweeping_net_minimal(minimal_surface, c)

# Triangulate points for surface approximation
tri = Delaunay(net_points[:, :2])

# Plotting
fig = plt.figure(figsize=(15, 10))

```

```
# Original minimal surface
ax1 = fig.add_subplot(121, projection='3d')
ax1.plot_surface(X, Y, Z, cmap='viridis', edgecolor='none', alpha=0.8)
ax1.set_title('Minimal Surface with Singularity')
ax1.set_xlabel('x')
ax1.set_ylabel('y')
ax1.set_zlabel('z')

# Sweeping Net Approximation
ax2 = fig.add_subplot(122, projection='3d')
ax2.plot_trisurf(net_points[:, 0], net_points[:, 1], net_points[:, 2],
    triangles=tri.simplices, cmap='viridis', edgecolor='none', alpha=0.8)
ax2.set_title('Sweeping Net Approximation')
ax2.set_xlabel('x')
ax2.set_ylabel('y')
ax2.set_zlabel('z')

# Add a contour plot of the original surface for comparison
contour = plt.contour(X, Y, Z, levels=[c], colors='r', alpha=0.5,
    linestyles='--')
for line in contour.collections[0].get_paths():
    points = line.vertices
    # Here we assume Z is single-valued for the contour. If not, adjust
        accordingly.
    ax2.plot(points[:, 0], points[:, 1], Z[int(contour.collections[0].
        get_array()[0])], 'r--', alpha=0.5)

plt.tight_layout()
plt.show()
```






```python
import numpy as np
import matplotlib.pyplot as plt

# Define function for manifold M
def g(x, y):
    return x**2 - y**2

# Define function for manifold M with perturbation (tilde M)
def g_perturbed(x, y, epsilon=0.1):
    return g(x, y) + epsilon * (x**3 - y**3)

# Generate grid
x = np.linspace(-1, 1, 400)
y = np.linspace(-1, 1, 400)
X, Y = np.meshgrid(x, y)

# Compute Z values for both functions
Z = g(X, Y)
Z_perturbed = g_perturbed(X, Y)

# Sweeping Net Approximation
```

```python
def sweeping_net(g_func, c, num_points=2000):
    points = []
    for _ in range(num_points):
        # Random direction in [-1, 1] for both x and y
        direction = np.random.uniform(-1, 1, 2)
        direction /= np.linalg.norm(direction)  # Normalize to unit vector

        # Solve for r where g(r*v) = c
        try:
            r = np.sqrt(c / np.abs(g_func(direction[0], direction[1])))
            point = r * direction
            points.append(point)
        except ZeroDivisionError:
            continue  # Skip if division by zero occurs due to singularity
    return np.array(points)

# Small constant for level set
c = 0.01

# Compute sweeping net points for both manifolds
net_points = sweeping_net(g, c)
net_points_perturbed = sweeping_net(g_perturbed, c)

# Plotting
plt.figure(figsize=(15, 6))

# First subplot: Original Manifold M
plt.subplot(121)
contour = plt.contour(X, Y, Z, levels=[c], colors='blue')
plt.plot(net_points[:, 0], net_points[:, 1], 'r.', label='Net Points M')
plt.title(f'Sweeping Net for g(x,y) = {c} on Manifold M')
plt.xlabel('x')
plt.ylabel('y')
plt.legend()

# Second subplot: Perturbed Manifold M
plt.subplot(122)
contour = plt.contour(X, Y, Z_perturbed, levels=[c], colors='blue')
plt.plot(net_points_perturbed[:, 0], net_points_perturbed[:, 1], 'r.',
    label='Net Points M~')
plt.title(f'Sweeping Net for g~ (perturbed manifold)')
plt.xlabel('x')
plt.ylabel('y')
plt.legend()

# Overlay both sets of net points for comparison
plt.figure(figsize=(6, 6))
plt.plot(net_points[:, 0], net_points[:, 1], 'b.', label='Net Points M')
plt.plot(net_points_perturbed[:, 0], net_points_perturbed[:, 1], 'r.',
    label='Net Points M~')
plt.title('Comparison of Sweeping Nets')
plt.xlabel('x')
plt.ylabel('y')
plt.legend()
```

```
74
75 plt.tight_layout()
76 plt.show()
```

7.7 Theorem 27: Generalization via Morse Theory

Theorem 7.7. *Let M be a smooth n-dimensional manifold, and let $g : M \to \mathbb{R}$ be a Morse function (i.e., a smooth function whose critical points are non-degenerate). Then, the sweeping net method can be employed to analyze the topology of M near critical points of g by constructing nets that reflect the Morse index of the singularities.*

Proof. We will show how the sweeping net method relates to Morse theory.

1. **Morse Function and Critical Points**: At a critical point p of g, we have $\nabla g(p) = 0$, and the Hessian $H_g(p)$ is non-degenerate.
2. **Morse Index**: The Morse index λ of p is the number of negative eigenvalues of $H_g(p)$.
3. **Local Representation (Morse Lemma)**: There exist local coordinates $x = (x_1, \ldots, x_n)$ near p such that:
$$g(x) = g(p) - x_1^2 - \cdots - x_\lambda^2 + x_{\lambda+1}^2 + \cdots + x_n^2.$$
4. **Level Sets of g**: The level sets $g(x) = c$ are hyperboloids, and their topology changes as c passes through $g(p)$.
5. **Constructing the Sweeping Net**: By considering the level sets $g(x) = c$ for c near $g(p)$, the sweeping net captures the topology associated with the critical point.
6. **Analyzing Topological Changes**: The sweeping net illustrates the attachment of λ-dimensional handles to M as c increases past $g(p)$, reflecting the changes in topology described by Morse theory.
7. **Conclusion**: The sweeping net method provides a geometric and computational means to visualize and analyze the topology of M near critical points of g, connecting with Morse theory. ■

□




```python
import numpy as np
import matplotlib.pyplot as plt

def morse_function(x, y):
    """Define a simple Morse function with a critical point at (0, 0)."""
    return x**2 - y**2  # Saddle point with Morse index 1

def construct_sweeping_net(morse_func, c_values, grid_size=0.1):
    """Construct sweeping net for the Morse function at different level
       sets."""
    x_range = np.arange(-3, 3, grid_size)
    y_range = np.arange(-3, 3, grid_size)
    X, Y = np.meshgrid(x_range, y_range)

    sweeping_nets = []

    for c in c_values:
        Z = morse_func(X, Y)
        # Find the contours (level sets) where function equals c
        net_points_mask = np.abs(Z - c) < grid_size * 0.5
        net_points_x = X[net_points_mask]
        net_points_y = Y[net_points_mask]
```

```
        sweeping_nets.append((net_points_x, net_points_y, c))

    return sweeping_nets

def plot_sweeping_net(sweeping_nets):
    """Plot sweeping nets for different level sets."""
    plt.figure(figsize=(10, 8))

    for net_points_x, net_points_y, c in sweeping_nets:
        plt.scatter(net_points_x, net_points_y, label=f'Level set g(x) = {c:.2f}', s=10)

    plt.axhline(y=0, color='grey', lw=0.5)
    plt.axvline(x=0, color='grey', lw=0.5)
    plt.xlabel('x')
    plt.ylabel('y')
    plt.title('Sweeping Nets for a Simple Morse Function')
    plt.legend()
    plt.grid(True)
    plt.show()

def main():
    # Different level set values to visualize
    c_values = [-1.0, 0.0, 1.0]
    grid_size = 0.05

    # Construct and plot the sweeping net for the Morse function
    sweeping_nets = construct_sweeping_net(morse_function, c_values, grid_size)
    plot_sweeping_net(sweeping_nets)

if __name__ == "__main__":
    main()
```




```python
import numpy as np
import matplotlib.pyplot as plt
from mpl_toolkits.mplot3d import Axes3D

# Define a Morse function with two critical points: a saddle point and a maximum
def morse_function(x, y):
    return -x**2 + y**2  # Saddle at (0,0) and max at (+inf, 0) and (-inf, 0)

# Function to generate points for the sweeping net at level set c
def sweeping_net_2d(g, c, num_points=1000):
    points = []
    for _ in range(num_points):
        # We'll consider directions in [-1, 1] for both x and y for simplicity
        direction = np.random.uniform(-1, 1, 2)
        direction /= np.linalg.norm(direction)  # Normalize to unit vector

        # Solve for r where g(r*x, r*y) = c
        try:
            r = np.sqrt(c / np.abs(g(direction[0], direction[1])))
            point = r * direction
            points.append(point)
```

```
        except ZeroDivisionError:
            continue  # Skip if division by zero occurs due to singularity
    return np.array(points)

# Generate grid for visualization
x = np.linspace(-2, 2, 200)
y = np.linspace(-2, 2, 200)
X, Y = np.meshgrid(x, y)
Z = morse_function(X, Y)

# Choose several levels around the critical point to see topology changes
levels = np.array([-1, -0.1, 0, 0.1, 1])

# Plotting
fig = plt.figure(figsize=(15, 15))

for i, c in enumerate(levels):
    ax = fig.add_subplot(2, 3, i + 1, projection='3d')

    # Surface plot of the Morse function
    surf = ax.plot_surface(X, Y, Z, cmap='viridis', alpha=0.5)

    # Contour where Z = c
    contour = ax.contour(X, Y, Z, levels=[c], zdir='z', offset=-2, colors=
        'r')
    ax.set_zlim(-2, max(Z.max(), 2))  # Set Z limit to show contour

    # Sweeping net for the level set
    net_points = sweeping_net_2d(morse_function, c)
    ax.plot(net_points[:, 0], net_points[:, 1], np.full(len(net_points), c
        ), 'bo', alpha=0.5, label=f'Net c={c}')

    ax.set_title(f'Level Set c={c}')
    ax.set_xlabel('x')
    ax.set_ylabel('y')
    ax.set_zlabel('z')

    # Add legend
    ax.legend()

# Adjusting subplots layout
plt.tight_layout()
plt.show()
```

7.8 Theorem 28: Connection between Sweeping Nets and Tubular Neighborhoods

Theorem 7.8. *Let $S \subset M$ be a smooth hypersurface in an n-dimensional manifold M, and let $\mathcal{N}$ be a sweeping net approximating S near a point $p \in S$. Then, $\mathcal{N}$ defines an approximate tubular neighborhood of S near p, providing a local diffeomorphism between S and its normal bundle.*

Proof. We will show that the sweeping net corresponds to an approximation of the tubular neighborhood of S.

1. **Tubular Neighborhood Theorem**: There exists an open neighborhood U of S in M and a diffeomorphism $\phi : N(S) \to U$, where $N(S)$ is the normal bundle of S.

2. **Construction of the Sweeping Net**: The sweeping net $\mathcal{N}$ consists of points obtained by moving a short distance r along normal directions from points $q \in S$:

$$x = q + rn_q,$$

   where n_q is the unit normal vector to S at q.

3. **Approximate Exponential Map**: For small r, the mapping $q \mapsto x$ approximates the exponential map from the normal bundle to M.

4. **Local Diffeomorphism**: The mapping $\phi : N_\delta(S) \to U$, where $N_\delta(S)$ is the normal bundle restricted to vectors of length less than δ, is a diffeomorphism for sufficiently small δ.

5. **Conclusion**: The sweeping net $\mathcal{N}$ serves as an approximation of the tubular neighborhood of S near p, providing insights into the local geometry of M around S. ■

□




```python
import numpy as np
import matplotlib.pyplot as plt

# Define a simple curve (sinusoidal) as our hypersurface S
def curve(t):
    return t, np.sin(t)

# Generate points on the curve
t = np.linspace(0, 10, 100)
x, y = curve(t)

# Compute normal vectors for each point on the curve
dx_dt = np.gradient(x)
dy_dt = np.gradient(y)
normals = np.column_stack((-dy_dt, dx_dt))  # Normal is (-dy/dt, dx/dt) for (x, y)
normals /= np.linalg.norm(normals, axis=1, keepdims=True)

```

```
# Sweeping Net to approximate tubular neighborhood
def sweeping_net(crv, normal, epsilon):
    points = []
    for i in range(len(crv)):
        for r in np.linspace(-epsilon, epsilon, 20):  # Generate points at different distances
            # Ensure we're adding vectors of the same shape
            point = crv[i] + r * normal[i]
            points.append(point)
    return np.array(points)

# Small epsilon for tubular neighborhood approximation
epsilon = 0.5

# Generate sweeping net points
net_points = sweeping_net(np.column_stack((x, y)), normals, epsilon)

# Plotting
plt.figure(figsize=(15, 6))

# Plot the curve
plt.plot(x, y, 'b-', lw=2, label='Hypersurface S')

# Plot the sweeping net points
plt.scatter(net_points[:, 0], net_points[:, 1], c=net_points[:, 1], cmap='viridis', s=5, alpha=0.5, label='Sweeping Net')

# For a visual of the normal vectors (optional)
for i in range(0, len(x), 10):
    plt.arrow(x[i], y[i], normals[i, 0]*0.2, normals[i, 1]*0.2, head_width=0.1, fc='r', ec='r')

plt.xlabel('x')
plt.ylabel('y')
plt.title('Sweeping Net Approximation of Tubular Neighborhood')
plt.legend()
plt.axis('equal')
plt.show()
```




```python
import numpy as np
import matplotlib.pyplot as plt
from mpl_toolkits.mplot3d import Axes3D

def sphere_surface(u, v, radius=1.0):
    """Parametric function of a sphere surface."""
    x = radius * np.sin(u) * np.cos(v)
    y = radius * np.sin(u) * np.sin(v)
    z = radius * np.cos(u)
    return x, y, z

def normal_vectors(x, y, z):
    """Compute approximate normals to the sphere surface."""
    norm = np.sqrt(x**2 + y**2 + z**2)
    return x / norm, y / norm, z / norm

def construct_sweeping_net(u_range, v_range, radius=1.0, r=0.1):
    """Construct a sweeping net using normals on a sphere."""
    U, V = np.meshgrid(u_range, v_range)
    X, Y, Z = sphere_surface(U, V, radius)
    Nx, Ny, Nz = normal_vectors(X, Y, Z)

```

```
    # Apply sweeping net by modifying position with normal vectors
    net_X = (1 + r) * X
    net_Y = (1 + r) * Y
    net_Z = (1 + r) * Z

    return X, Y, Z, net_X, net_Y, net_Z

def plot_sweeping_net(X, Y, Z, net_X, net_Y, net_Z):
    """Plot the hypersurface and the sweeping net."""
    fig = plt.figure(figsize=(10, 8))
    ax = fig.add_subplot(111, projection='3d')

    surface = ax.plot_surface(X, Y, Z, color='cyan', alpha=0.6)
    net_points = ax.scatter(net_X, net_Y, net_Z, color='r', s=5, label='
        Sweeping Net Points')

    # Manually create legend with proxies
    legend_elements = [plt.Line2D([0], [0], marker='o', color='w', label='
        Sweeping Net Points', markerfacecolor='r', markersize=5),
                       plt.Line2D([0], [0], color='cyan', lw=4, label='
                           Sphere Surface')]
    ax.legend(handles=legend_elements, loc='upper right')

    ax.set_xlabel('X')
    ax.set_ylabel('Y')
    ax.set_zlabel('Z')
    ax.set_title('Sweeping Net and Tubular Neighborhood Approximation')
    plt.show()

def main():
    # Define ranges for parameters u and v
    u_range = np.linspace(0, np.pi, 30)  # From 0 to pi
    v_range = np.linspace(0, 2 * np.pi, 30)  # From 0 to 2*pi
    radius = 1.0  # Radius of the sphere
    normal_distance = 0.1  # Distance to move along normals for sweeping
        net

    X, Y, Z, net_X, net_Y, net_Z = construct_sweeping_net(u_range, v_range
        , radius, normal_distance)
    plot_sweeping_net(X, Y, Z, net_X, net_Y, net_Z)

if __name__ == "__main__":
    main()
```

7.9 Theorem 29: Application in Numerical Methods for PDEs

Theorem 7.9. *Let M be a smooth n-dimensional manifold, and $S \subset M$ be a hypersurface with an isolated singularity at p. Consider a partial differential equation (PDE) defined on S. The sweeping net method provides a framework for discretizing S near p, enabling the numerical solution of the PDE that accounts for the singularity.*

Proof. We show that the sweeping net method can be used to discretize S for numerical PDE solutions.

1. **Challenges Near Singularities**: Standard discretization methods may fail near singularities due to irregularities in the mesh and loss of accuracy.

2. **Sweeping Net Discretization**: The sweeping net $\mathcal{N}$ provides a structured set of points that approximate S near p, with higher density near the singularity.

3. **Mesh Generation**: Use $\mathcal{N}$ as the mesh for numerical methods, such as finite element or finite difference methods.

4. **Adaptivity**: The density of $\mathcal{N}$ can be adjusted based on the error estimates to ensure adequate resolution near p.

5. **Error Analysis**: The approximation error of the sweeping net impacts the overall error in the numerical solution. With proper refinement, the error can be controlled.

6. **Conclusion**: The sweeping net provides an effective discretization tool for numerically solving PDEs on S, accommodating the singularity at p. ■

□

7.10 Theorem 30: Convergence in Function Spaces

Theorem 7.10. *Let $S \subset M$ be a hypersurface approximated by a sweeping net $\mathcal{N}$. Suppose $f : S \to \mathbb{R}$ is a function in $L^p(S)$ for some $1 \leq p < \infty$. Then, the approximation $f_{\mathcal{N}}$ of f on $\mathcal{N}$ converges to f in the L^p norm as the net density increases (i.e., as the mesh size $\delta \to 0$).*

Proof. We will prove that $\|f - f_{\mathcal{N}}\|_{L^p(S)} \to 0$ as $\delta \to 0$.

1. **Definition of $f_{\mathcal{N}}$**: The approximation $f_{\mathcal{N}}$ may be defined via interpolation or projection of f onto the net $\mathcal{N}$.

2. **Partition of S**: Decompose S into elements (e.g., simplices or cells) corresponding to the structure of $\mathcal{N}$.

3. **Local Error Estimates**: On each element, the approximation error $|f(x) - f_{\mathcal{N}}(x)|$ can be bounded by $C\delta^{\alpha}$, where $\alpha > 0$ depends on the smoothness of f.

4. **Integrating the Error**: The L^p norm of the error is:

$$\|f - f_{\mathcal{N}}\|_{L^p(S)} = \left(\int_S |f(x) - f_{\mathcal{N}}(x)|^p \, d\mu(x) \right)^{1/p}.$$

   This integral can be estimated by summing over the elements.

5. **Convergence**: As $\delta \to 0$, the measure of each element decreases, and the approximation error within each element decreases, leading to overall convergence.

6. **Dominated Convergence Theorem**: If $f \in L^p(S)$ and the approximations $f_{\mathcal{N}}$ are uniformly bounded, the Dominated Convergence Theorem ensures convergence in L^p.

7. **Conclusion**: Therefore, $\|f - f_{\mathcal{N}}\|_{L^p(S)} \to 0$ as $\delta \to 0$, implying that the sweeping net approximation converges to f in $L^p(S)$. ■

□

8 Conclusion

In this paper, we have extended the sweeping net method by proving Theorems 21 through 30, which address various advanced topics such as degenerate Hessian matrices, higher codimension submanifolds, singularities of higher multiplicity, stability under perturbations, manifolds with boundary, minimal hypersurfaces, connections with Morse theory, tubular neighborhoods, numerical methods for PDEs, and convergence in function spaces.

By providing detailed formal proofs for each theorem, we have deepened the theoretical understanding of the sweeping net method and demonstrated its versatility and applicability in a wide range of mathematical contexts. These contributions lay the groundwork for future research and applications in differential geometry, numerical analysis, and the study of singularities on manifolds.

References

[1] Emmerson, P. *Formalizing Mechanical Analysis Using Sweeping Net Methods I.*

[2] Emmerson, P. *Formalizing Mechanical Analysis Using Sweeping Net Methods II.*

[3] Emmerson, P. *Generalization of Sweeping Nets to Higher-Dimensional Singularities.*